



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification ⁶ : B32B 3/02	A1	(11) International Publication Number: WO 98/49000 (43) International Publication Date: 5 November 1998 (05.11.98)
<p>(21) International Application Number: PCT/US98/08634</p> <p>(22) International Filing Date: 29 April 1998 (29.04.98)</p> <p>(30) Priority Data: 08/840,395 29 April 1997 (29.04.97) US</p> <p>(71) Applicant: DARWIN ENTERPRISES, INC. [US/US]; P.O. Box 3992, Dalton, GA 30719 (US).</p> <p>(71)(72) Applicant and Inventor: LINVILLE, Steve [US/US]; 2929 Sagebrush Drive, Flower Mound, TX 75028 (US).</p> <p>(72) Inventor: IRWIN, Donald, A., Sr.; 107 Azalea Drive, Dalton, GA 30721 (US).</p> <p>(74) Agent: MIDDLETON, James, B.; P.O. Box 1968, Decatur, GA 30031-1968 (US).</p>	<p>(81) Designated States: AU, BB, BG, BR, BY, CH, CZ, FI, HU, JP, KP, KR, KZ, LK, MG, MN, MW, NO, NZ, PL, RO, RU, SD, SK, UA, VN, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>	

(54) Title: DIMENSIONALLY STABLE TUFTED CARPET

(57) Abstract

A carpet (10) is tufted (11) with a two-part primary backing (12). The upper, or face, backing (14) is a conventional woven or non-woven polypropylene, and the lower, or back, backing (15) is a stronger, open weave fabric. The tufts of yarn (11) are sewn through both parts of the primary backing (12), which holds the parts (14, 15) together, and causes some of the back stitches to protrude for better coating with adhesive. The resulting carpet may be fully back coated, and may have a secondary backing adhered thereto.

The lower backing prevents elongation, stretching and shrinking of the carpet during manufacture and subsequent processing.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

-1-

DIMENSIONALLY STABLE TUFTED CARPET

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates generally to carpets and the like, and is more particularly concerned with a tufted carpet having a double primary backing for providing a dimensionally stable carpet before coating, and without application of a secondary backing.

Discussion of the Prior Art

10 In the past, tufted carpeting was made by tufting yarn into a backing of woven jute or the like. The jute backing was heavy and stable, so one coated the back with latex or other adhesive only to lock in the tufts, and the carpet was ready to install. More recently, however, various light weight materials have been used as a primary backing through which yarn is tufted, and a secondary backing of a stable material is adhered to the back of the carpet by an adhesive.

Currently, the most popular primary backings are 20 polypropylene, either woven or non-woven materials. Such backings are preferred because: they are inexpensive; the material has an oily quality that provides for smooth entry and exit of the needles; and, the material is quite elastic so the hole tends to 25 close around the yarn after the needle is withdrawn.

However, the polypropylene has some disadvantages. Those skilled in the art will realize that polypropylene is a thermoplastic-elastomer, so the backing is subject to degradation by excess heat, and 30 is rather easily stretched through the application of tension.

Typically, after face yarns are tufted into a primary backing, the resulting carpet is back coated

-2-

with an adhesive to lock in the stitches. Without the back coating, the tufts are very easy to pull out, so the back coating is an important next step. During the coating, however, the carpet is unstable because there is only the primary backing. Thus, one experiences generally from 5 to 20% elongation of the carpet during the back coating process. While this creates more carpet, it also reduces the amount of face yarn per unit area. Furthermore, the backing may not stretch uniformly, so any pattern in the carpet will be distorted. There have been efforts at holding the pattern straight, but such efforts require additional equipment and effort, and still do not solve the basic problem of stretching of the primary backing.

15 The prior art includes some rugs or carpets having a plurality of backings. For example, U.S. Patent No. 2,713,012 to Hartstein discloses a tufted rug having dual primary backings of cotton and jute or the like. The Hartstein patent does not contemplate back coating of the rug, and relies on the double backing to assist in holding in the tufts. Also, the jute backing is heavy enough to stabilize the rug. U.S. Patent No. 4,426,415 to Avery discloses a carpet in the nature of artificial turf having a plurality of primary backings, the backings varying in fineness from bottom to top of the carpet. All of the plurality of backings are of the same material, and polypropylene is specifically mentioned. Since Avery contemplates back coating of the carpet, the problem of stretching and distorting will still be present, though perhaps slightly reduced because of the greater strength of multiple backings. U.S. Patent No. 4,705,706 to Avery discloses a multiple primary backing, but the backing may be nylon or the like while the face yarn is polyethylene so the back

-3-

stitch can be set by heat rather than by a separately applied adhesive. The multiple layers of backing, then, allow sand to infiltrate when the carpet is used as outdoor turf.

5 It will therefore be seen that the prior art has not provided a solution to the problem of stretching and distorting of the carpet during back coating and other treatment of the carpet.

SUMMARY OF THE INVENTION

10 The present invention provides a tufted carpet having a double primary backing, one part of such backing being a conventional backing of polypropylene or the like, and the other part being an open weave material having greater strength and less stretch than
15 the conventional backing. The face yarns are tufted through both parts of the double backing, which secures the two backings together. In view of the open weave in the other part of the backing at least some of the back stitches protrude noticeably from the back of the
20 carpet, so applied adhesive can truly encapsulate such stitches for maximum strength.

With the dual primary backing, it has been found that the tufts are held more securely, even before back coating of the carpet, so the carpet can be handled as
25 necessary without fear of losing any substantial amount of face yarns. During back coating or other processing of the carpet, the non-stretchable backing in the carpet prevents elongation or other stretching of the carpets. As a result, the quality of the carpet,
30 including the integrity of the pattern and the quantity of face yarns per unit area, remains consistent.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the present invention will become apparent from

-4-

consideration of the following specification when taken in conjunction with the accompanying drawings in which:

Fig. 1 is a perspective view showing a piece of carpet made in accordance with the present invention, 5 the carpet being partially broken away to show the construction;

Fig. 2 is a schematic illustration showing the tufting of carpet in accordance with the present invention;

10 Fig. 3. is a highly enlarged cross-sectional view showing the construction of carpet made in accordance with the present invention;

Fig. 4 is a view similar to Fig. 3, but showing an adhesive in place to lock in the stitches;

15 Fig. 5 is a view similar to Fig. 4 but showing a secondary backing placed over the adhesive; and,

Fig. 6 is a schematic illustration showing a plan view of the back of a carpet made in accordance with the present invention.

20 DETAILED DESCRIPTION OF THE EMBODIMENTS

Referring now more particularly to the drawings, and to those embodiments of the invention here presented by way of illustration, Fig. 1 shows a piece of carpet generally designated at 10, the carpet 10 comprising 25 face yarns 11 and a primary backing 12. The primary backing comprises an upper backing 14 and a lower backing 15. The term "upper backing" as used herein indicates the backing at the face of the carpet. Similarly, the term "lower backing" indicates the 30 backing on the bottom when the carpet is laid.

The upper backing 14 is here indicated as a woven material, but it will be understood that it may equally well be a non-woven material. It is contemplated that the upper backing 14 will be a conventional primary

-5-

backing material of polypropylene. Such backings utilize a relatively soft polypropylene so the tufting needles will penetrate easily, but such backings are inherently unstable dimensionally. Those skilled in the art will realize that the backing 14 is most often woven from polypropylene ribbons.

The lower backing 15 is here indicated as an open weave material. It is contemplated that the backing 15 may comprise a leno weave having mono-filaments or tape yarn in the warp direction, and a spun fiber in the fill direction. While this construction is not necessary, the mono-filaments or tape will yield a high degree of non-stretchability, while the spun fibers will increase adhesion between the backing 15 and the adhesive used to back coat the carpet 10.

For maximum stability of the carpet of the present invention, the lower backing 15 may be formed of fiber glass or the like; however, one can attain the objects of the invention with other materials, though with some sacrifice in stability. Thus, one might use a polypropylene lower backing 15, but the backing 15 will still be an open weave as shown, and still be a leno weave or similar construction to yield reasonable dimensional stability. Furthermore, the particular polypropylene used will preferably be a harder material having greater strength and less stretch than the soft material used in the conventional primary backing. Similarly, other materials having less stretch may be used, such as polyester or other polymeric materials. Of course the number of picks per inch in the fabric can be varied along with the particular fiber to attain the desired quality and cost.

With attention directed to Fig. 2 of the drawings, it will be understood that the carpet of the present

-6-

invention is tufted in a generally conventional way. The usual primary backing, the upper backing 14, is mounted on a roll 16, and passes through the tufting machine to the exit rolls 18. In accordance with the present invention, the lower part of the primary backing 15 is mounted on a roll 19, and is held against the backing 14 by a roll 20. With the two parts of the backing 12 held together, the tufting machine sews tufts of yarn through the primary backing 12. It will therefore be understood that the carpet, immediately on being tufted, has the strength and stability attributes discussed above. Those skilled in the art will realize that carpet may be stretched and distorted as it emerges from the tufting machine, but the present invention substantially eliminates such stretch and distortion.

A constant concern in the tufting process is needle deflection. If some of the needles engage fibers or the like, and some needles move laterally in attempting to penetrate, there is a danger of breaking a needle, and there is a great danger of producing deviant stitches that reduce the quality of the finished goods. Those skilled in the art have always thought that one could not tuft into a material such as the backing 15 because of needle deflection. One has used very soft polypropylene ribbons, or spun fibers, or soft non-woven polypropylene as a primary backing. In developing the carpet of the present invention, open weave fabrics of a hard polypropylene, and even fiber glass, have been tufted into without experiencing any needle deflection.

For a more thorough understanding of the construction of the carpet of the present invention, attention is directed to Fig. 3 of the drawings. It

-7-

will be seen that the tufts of the face yarn 11 pass through the primary backing 12. In more detail, the yarn of the tufts 21 passes through both the upper backing 14 and the lower backing 15, and the stitches making up the back stitch 22 loops over the strands of the lower backing 15.

Since the backing 15 is an open weave, some of the stitches are likely to miss the strands of the backing 15 and engage only the backing 14. In Fig. 3 the yarns of the tufts 24 pass through only the upper backing 14, and the back stitches 25 lie against the lower side of the backing 15. This is further illustrated in Fig. 6 of the drawings where the back stitches 22' are shown looping over the strands of the lower backing 15, while some of the back stitches 25' are shown between the strands of the backing 15, and engaged with only the upper backing 14.

In view of the construction described above, it will be understood that the tufts of yarn are mechanically locked into the system. In the conventional tufted carpet, the tufts are, like the tuft 24, through only the soft and stretchable material 14, but without the additional fabric 15 to hold the tufts. The carpet 10, having the second primary backing 15, does not stretch or distort noticeably, but is stable even as it leaves the tufting machine.

In the above and foregoing discussion, it should be understood that the term "primary backing" indicates a sheet of material through which yarns are inserted. The term "secondary backing" indicates a sheet of material that is fixed to the back of the tufted carpet, such material not having yarns inserted therethrough.

Those skilled in the art will realize that, even

-8-

with the mechanical lock for the tufts 21 and 24, it is desirable to back coat the carpet to assure that the tufts will not pull out. One form of back coating utilizes a small amount of adhesive, and the adhesive
5 is allowed to coat the back stitch very lightly. The carpet of the present invention works well with such back coating because stitches such as the stitches 22 and 22' stand out from the backing, allowing the adhesive to coat the sides of the stitches. Many
10 adhesives used do not actually adhere well to the fiber, but depend on simply encapsulating the stitches to prevent their pulling out. With the protruding stitches 22 and 22', the yarns can be well encapsulated for firm anchoring of the yarns.

15 Sometimes it is preferable to back coat the carpet to provide a smooth rear surface, as shown in Fig. 4. Fig. 4 is like Fig. 3, except that there is a coating of adhesive 26. The adhesive 26 is thick enough that the entire back stitch is covered, and the back of the
20 carpet is smooth.

Fig. 5 shows a modified form of the carpet shown in Fig. 4. In Fig. 5, the adhesive 26 is present, and the adhesive is also used to adhere a secondary backing 28 to the carpet. While a secondary backing will not be
25 required on the carpet of the present invention for most uses, one may wish to use a tricot as a secondary backing for installations using hook and loop fasteners for holding carpet. In this event, the tricot secondary backing performs the function of the loop
30 material for fastening the carpet to the floor.

The carpet as shown in fig. 5 may have other sheet materials adhered thereto as a secondary backing. For example, one might select any of the conventional woven or non-woven materials, or a sheet of foamed material.

The foamed material may be mechanically frothed and applied, may be foamed in place, or may be formed as a sheet and subsequently adhered to the carpet. All these techniques are known in the art. Further, one might use a waterproof barrier as disclosed in U.S. Patent No. 5,612,113. Other secondary backings will suggest themselves to those skilled in the art.

The invention will be understood better from consideration of the following examples:

10 Example I

A carpet was tufted at 56 ounces of face yarn per square yard, with a nylon fiber having a denier of 4400. The backing comprises a 15 foot wide primary backing "Poly Bac" style 2225 from Amoco Fabric and 15 Fibers Company, plus a layer of fiber glass, style 4802 from CCX Fiberglass Products. The tufting was performed on a 3/16 gauge tufting machine. No shrinkage was observed in this example, but a two- to three-inch shrinkage was observed without the layer of 20 fiber glass.

The tufted carpet described above was back coated with a polyurethane having the following formulation:

	Ingredient	Parts/Hundred
25	Arco Chemical Froth Polyol	92.
	Diethylene Glycol	8.
	Catalyst SC-561/5	1.
	Silicone L-5614	0.5
	Black	0.05
	Aluminum trihydrate	200.
30	Water	0.2
	Isocyanate Bayer E-448	64.

The process for applying the polyurethane coating is well known in the art, and is described in: Union Carbide patents numbers 3,772,224, 3,849,156,

-10-

3,947,386, and 4,022,941; Dow Chemical patents numbers 5,104,693 and 4,853,054; and, Bayer patent number 4,035,529.

Example II

5 The carpet of example I was tufted using an open weave polypropylene "Action Bac" style 3870 from Amoco Fabrics and Fibers Company in place of the fiberglass.

Example III

The carpet of Example I was tufted using an open
10 weave polyester fabric in place of the fiberglass.

The results of the Example II and Example III carpets are as follows:

	Example II	Example III
Tensile--Warp	359.	405.
15 Elongation--Warp	25.7	6.0
Tensile--Fill	346.2	375.
Elongation--Fill	25.2	5.5

Example IV

A carpet was tufted at 32 ounces per square yard
20 with a nylon fiber having a denier of 3750. The backing comprised a 12 foot wide "Poly Bac" Style 2200 From Amoco Fabrics and Fibers Company plus an open weave fabric of propylene style 3870 from Amoco Fabrics and Fibers Company. The carpet was tufted on a 1/8
25 gauge tufting machine. No shrinkage was measured.

The resulting carpet was back coated with a latex containing 125 parts calcium carbonate, at 32 ounces per square yard. During the backing process, the carpet shrank only 1/4 inch, as opposed to 3 to 6
30 inches for normal carpet. Additionally, the carpet had a tuft bind of 22.4 pounds versus 17.6 pounds for the same carpet with a single primary backing.

From the foregoing it will be understood that the present invention provides a carpet having a superior

-11-

dimensional stability from the time of tufting, through coating, and through installation and use. The carpet is not as severely affected by stress during coating, nor by heat during coating or curing. Even without the
5 application of a secondary backing, the carpet of the present invention can be stretched into place, or can be glued down, without fear of stretch causing unsightly bulges.

It will of course be understood by those skilled in
10 the art that the particular embodiments of the invention here presented are by way of illustration only, and are meant to be in no way restrictive; therefore, numerous changes and modifications may be made, and the full use of equivalents resorted to,
15 without departing from the spirit or scope of the invention as outlined in the appended claims.

20

25

30

-12-

WHAT IS CLAIMED AS INVENTION IS:

1. In a tufted carpet comprising a primary backing,
and a plurality of tufts of yarn sewn through said
primary backing and exposed on a first side of said
5 primary backing for forming face yarns, said tufts of
yarn forming a plurality of stitches on the opposite
side of said primary backing for forming a back stitch,
the improvement wherein said primary backing comprises
a first backing formed of a thermoplastic material,
10 and a second backing having warp yarns and fill yarns
with at least said warp yarns formed of a material
stronger and less stretchable than said first backing,
said second backing having an open weave, said first
backing and said second backing being contiguous with
15 each other, with said first backing forming said first
side of said primary backing and said second backing
forming said second side of said primary backing, and
said tufts of yarn securing said first backing to said
second backing.
- 20 2. In a tufted carpet as claimed in claim 1, the
further improvement wherein at least some stitches of
said plurality of stitches pass over said yarns of said
second backing, holding said stitches away from said
first backing, and including an adhesive encapsulating
25 said stitches.
3. In a tufted carpet as claimed in claim 1 wherein
said first backing comprises a woven ribbon type
polypropylene, and including the improvement wherein
said second backing comprises a leno type weave.
- 30 4. In a tufted carpet as claimed in claim 3, the
improvement wherein said warp yarns are selected from
the group consisting of polypropylene, polyester,
nylon, cotton, fiber glass, and combinations thereof.
5. In a tufted carpet as claimed in claim 3, the

-13-

improvement wherein said warp yarns are selected from the group consisting of ribbons and monofilaments, and said fill yarns are spun yarns.

6. In a tufted carpet as claimed in claim 2, the
5 improvement wherein said adhesive coats the entire other surface of said primary backing, and said adhesive is selected from the group consisting of polyurethane, latex, a hot melt adhesive, and polyvinyl chloride.

10 7. In a tufted carpet as claimed in claim 6, the further improvement including a secondary backing adhered to said adhesive, said secondary backing being selected from the group consisting of a woven fabric, a non-woven fabric, a tricot, a waterproof sheet
15 material, and a foam layer.

8. A method for making a dimensionally stable tufted carpet, said tufted carpet comprising a primary backing having tufts of yarn sewn therein, said method comprising the steps of feeding a primary backing
20 through a tufting machine, said primary backing comprising a first layer consisting of a woven or non-woven polypropylene material and a second layer consisting of an open weave material having greater strength and less stretchability than said first layer,
25 sewing said tufts of yarn through both said layers for providing face yarns on said first layer and a back stitch on said second layer, and securing said first layer and said second layer together.

9. A method as claimed in claim 8, and further
30 including the step of back coating said tufted carpet for encapsulating said back stitch.

10. A method as claimed in claim 9, and including the step of applying a secondary backing against said back coating.

1/1




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US98/08634

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :B32B 3/02 US CL :428/95 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 428/95 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5,380,574 A (KATOH et al.) 10 January 1995, see entire document.	1-2 & 6-7
X	US 3,542,632 A (EICKHOFF) 24 November 1970, see entire document.	8-10
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* "A"	Special categories of cited documents: document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"B"	earlier document published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O"	document referring to an oral disclosure, use, exhibition or other means	
"P"	document published prior to the international filing date but later than the priority date claimed	"A" document member of the same patent family
Date of the actual completion of the international search 29 MAY 1998		Date of mailing of the international search report 27 JUL 1998
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer TERREL MORRIS Telephone No. (703) 308-2351